MerFen Security Ltd

FB4 Bullet Resistant Steel Access Door
FB4 - TB2

FB4 Access Door
Specification of Manufacture

Standard door size 990 x 2090 to suit structural opening 1000 x 2100mm or to suite specified opening size.

Normal structure 225mm re-enforced brick opening

Door standard outward opening left OR right hand hinged

Door Frame:

100 x 50 x 3mm RHS section sides and head, with 100 x 3mm bottom rail. Top corners mitred and continuously welded. Bottom rail full width welded both sides to 100 x 50 vertical sections. Door stop 50 x 25 x 3mm RHS stitch welded 50mm long at maximum 200mm centres. Bottom zero 564 rebated door threshold mechanically fixed to 100 x 3mm plate. RHS vertical rails drilled at maximum 300mm centres and countersunk for 10mm x 130mm frame anchors. Door frame seal to door stop zero 188S S/A teardrop seal.

Door Blank:

Nominal 46mm thick. Door core 80 x 40 x 3mm RHS section all round with centre 80 x 40 x 3mm horizontal brace positioned at centre of door. External 3mm steel sheet faces providing 20mm overhang

Address

MerFen Security Ltd
Unit L2, Gaywood Farm
Hole Lane
Edenbridge
Kent
TN8 6SL

Contact Information

info@merfensecurity.com

www.merfen-security.com

01732 926352